NSN 5935-01-191-9922

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-191-9922

Body Style:
Right angle type
Overall Length:
3.798 inches
Overall Height:
1.039 inches
Overall Width:
0.465 inches
Environmental Protection:
Cold resistant and heat resistant
Unthreaded Mounting Hole Diameter:
0.102 inches
Distance Between Mounting Facility Centers:
3.102 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Connector Locking Method:
Latch
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd
treatment response single mating end single contact grouping
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Hermaphrodite single mating end single contact grouping
Precious Material And Location:

0.050 gold grains, troy

Precious Material And Weight:

Contact surfaces gold

NSN 5935-01-191-9922

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.