Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-192-1289

#### **Body Style:**

Straight shape, external coupling

#### **Overall Length:**

1.542 inches

## **Overall Height:**

1.438 inches

## **Overall Width:**

1.438 inches

#### **Environmental Protection:**

Vibration resistant and thermal shock resistant and moisture resistant and shock resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.138 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

#### Distance From Mounting Shoulder To Front Face:

Between 0.814 inches and 0.820 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

19-32 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

200.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

# **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# NSN 5935-01-192-1289

Electrical Receptacle Connector - Page 2 of 2



Insert Materi	
Plastic single	-
	ace Treatment Specification:
Mil-g-45204 n	nilitary specification single treatment response single mating end single contact grouping
Terminal Typ	be:
Solder well si	ngle mating end single contact grouping
Contact Mate	erial Specification:
Qq-b-626 fed	eral specification single material response single mating end single contact grouping
Shell Materia	d:
Aluminum allo	ру
Shell Surface	e Treatment:
Nickel	
Shell Surface	e Treatment Specification:
Mil-c-26074 m	nilitary specification single treatment response
Shell Materia	Il Specification:
Qq-a-591 fed	eral specification single material response
Included Cor	ntact Quantity:
32 single mat	ing end single contact grouping
Included Cor	ntact Type:
Round pin sin	gle mating end single contact grouping
Precious Mat	terial And Location:
Contact surfa	ces gold
Precious Mat	terial And Weight:
0.032 gold gra	ains, troy
Precious Mat	terial:
Gold	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizat	ion:
No	
Fiig:	
A039b0	
Mil-std (milit	ary Standard):
Mil-g-45204 s	pec.