

View Online at <https://aerobasegroup.com/nsn/5935-01-192-4332>

Body Style:

Straight type

Overall Length:

3.710 inches

Overall Height:

0.556 inches

Overall Width:

0.450 inches

Environmental Protection:

Corrosion resistant and shock resistant and moisture resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.098 inches

Distance Between Mounting Facility Centers:

3.525 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 0 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping or mil-c-50 military specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, type gpt-30f military specification single material response single mating end

Included Contact Quantity:

98 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.098 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-50 spec.