Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-192-4334

| Thread Class: | |
|-------------------|--|
| 2a | |
| Thread Direction | on: |
| Right-hand | |
| Body Style: | |
| Straight shape, | external coupling |
| Overall Length | : |
| 1.638 inches | |
| Overall Height: | |
| Between 2.980 | inches and 3.021 inches |
| Overall Width: | |
| Between 2.980 | inches and 3.021 inches |
| Environmental | Protection: |
| Corrosion resist | ant and cold resistant and salt water resistant and waterproof |
| Unthreaded Mo | ounting Hole Diameter: |
| Between 0.206 | inches and 0.213 inches |
| Center To Cent | ter Distance Between Mounting Facilities Parallel To Height: |
| 2.375 inches | |
| Distance Betwo | een Centerlines Of Mounting Facilities Parallel To Body Width: |
| 2.375 inches | |
| Distance From | Mounting Shoulder To Front Face: |
| Between 0.922 | inches and 0.932 inches |
| Threaded Devi | се Туре: |
| Coupling facility | |
| Mating End Qu | antity: |
| 1 | |
| Contact Positio | on Arrangement Style: |
| 40-68 single ma | iting end |
| Contact Remov | vability: |
| Removable sing | le mating end single contact grouping |
| Contact Maxim | um Current Rating In Amps: |
| 46.0 single mati | ng end single contact grouping |
| Contact Maxim | um Ac Voltage Rating In Volts: |
| 500.0 single ma | ting end single contact grouping |
| Contact Maxim | um Dc Voltage Rating In Volts: |
| 700.0 single ma | ting end single contact grouping |
| Polarization Me | ethod: |
| Keyway or multi | ple keyway |
| Insert Position | In Deg: |
| 65.0 | |
| Shell Type: | |
| Solid | |



Connector Locking Method: Externally threaded shell **End Application:** An/tsq105v4 **Thread Length:** 0.672 inches Thready Qty Per Inch (tpi): 10 **Thread Size:** 2.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and nickel **Included Contact Quantity:** 21 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.021 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Double stub Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig:

A039b0