NSN 5935-01-192-8012

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-192-8012 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, flange mount **Overall Length:** 0.625 inches **Bushing Diameter:** 0.162 inches **Overall Height:** 1.080 inches **Unthreaded Mounting Hole Diameter:** 0.102 inches **Distance Between Mounting Facility Centers:** 0.481 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Osm single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping **Insert Material:** Plastic fluorocarbon single mating end

NSN 5935-01-192-8012

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A039b0