NSN 5935-01-192-8017

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-192-8017

View Online at https://aerobasegroup.com/nsn/5935-01-192-8017
Body Style:
Right angle type
Overall Length:
3.150 inches
Overall Width:
0.550 inches
Body Height:
0.250 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Contact
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290
class 2 federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Included Contact Quantity:
56 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping

Contact surfaces gold

Precious Material And Weight:

Precious Material And Location:

0.056 gold grains, troy

NSN 5935-01-192-8017

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.