NSN 5935-01-193-5135

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-193-5135

Body Style:
Straight shape, rectangular
Overall Length:
2.635 inches
Overall Height:
0.925 inches
Overall Width:
0.712 inches
Unthreaded Mounting Hole Diameter:
0.122 inches
Distance Between Mounting Facility Centers:
2.406 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
100.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tapered pin single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping

Steel

Shell Material:

NSN 5935-01-193-5135

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Tin and zinc
Shell Surface Treatment Specification:
Mil-t-10727a military specification 1st treatment response and qq-p-416 federal specification 2nd treatment response
Shell Material Specification:
Qq-s-698 federal specification single material response
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.