NSN 5935-01-193-5639

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-193-5639

| view Online at https://aerobasegroup.com/nsn/5955-01-195-5659 |
|-----------------------------------------------------------------------|
| Thread Class: |
| 2a and 2a |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.750 inches |
| Overall Diameter: |
| 1.954 inches |
| Environmental Protection: |
| Moisture resistant and vibration resistant |
| Distance From Mounting Shoulder To Front Face: |
| 0.879 inches |
| Mounting Facility Thickness: |
| Between 0.062 inches and 0.250 inches |
| Threaded Device Type: |
| Back shell and mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 22-95 single mating end |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Thready Qty Per Inch (tpi): |
| 18 and 18 |
| Thread Size: |
| 1.438 inches and 1.500 inches |
| Insert Material: |
| Rubber single mating end |
| Shell Material: |
| Aluminum |
| Shell Surface Treatment: |
| Chromate and cadmium |
| Shell Surface Treatment Specification: |
| Og n 416 type 2 class 2 foderal specification all treatment responses |

NSN 5935-01-193-5639

Electrical Receptacle Connector Body - Page 2 of 2



Fiig: A039b0