

View Online at <https://aerobasegroup.com/nsn/5935-01-193-5640>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

2.172 inches

Overall Diameter:

1.954 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Cable Entrance Diameter:

0.519 inches

Distance From Mounting Shoulder To Front Face:

0.884 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.250 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

22-14 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

19.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

End Application:

An/wlq- (v)

Thready Qty Per Inch (tpi):

18

Thread Size:

1.500 inches

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0