# NSN 5935-01-194-7570

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-194-7570

Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
6.220 inches
Overall Height:
0.734 inches
Overall Width:
0.366 inches
Environmental Protection:
Cold resistant and heat resistant and pressure proof and vibration resistant
Distance Between Mounting Facility Centers:
5.900 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
End Application:
7010-01-090-9923
Thread Size:
2.5 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 ty ii, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 2
federal specification 2nd treatment response single mating end single contact grouping

Crimp single mating end single contact grouping

**Terminal Type:** 

## NSN 5935-01-194-7570

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:
Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single
mating end
Thread Tolerance Class:
6g external
Unable To Decode:
Unable to decode and unable to decode and unable to decode
Included Contact Quantity:
60 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

100 contacts missing from insert

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.060 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Iso m

### Shelf Life:

N/a

#### **Unit Of Measure:**

#### Demilitarization:

No

# Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.