

NSN 5935-01-194-7576 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-194-7576 **Body Style:** Right angle type **Overall Length:** 7.100 inches **Overall Height:** 0.680 inches **Overall Width:**

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.068 inches

0.385 inches

Distance Between Mounting Facility Centers:

6.900 inches

Mating End Quantity:

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize

Included Contact Quantity:

198 single mating end single contact grouping

NSN 5935-01-194-7576

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Ty	pe:
----------	---------	----	-----

Flat pin single mating end single contact grouping

Special Features:

Contacts 133 through 198 have elongated blades

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.198 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0