## NSN 5935-01-194-7590

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-194-7590

2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape
Overall Length:
2.350 inches
Overall Height:
0.565 inches
Overall Width:
0.250 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant
Distance Between Mounting Facility Centers:
2.150 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

## NSN 5935-01-194-7590

Electrical Receptacle Connector - Page 2 of 2



Electrical Receptacle Confidential - Page 2 of 2	Grut
Criticality Code Instification	
Criticality Code Justification:	
Feat	
Terminal Type:	
Solder well single mating end single contact grouping	
Contact Material Specification:	
Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 fede	-
material response single mating end single contact grouping or qq-b-750 federal specification single material response si	onse single mating end
single contact grouping	
Insert Material Specification:	
Mil-p-46174, cl 40, grade e military specification single material response single mating end	
Included Contact Quantity:	
40 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Special Features:	
Weapon system essential	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.040 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unc and unc and unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Files	

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.