Electrical Plug Connector - Page 1 of 2





**Thread Class:** 2a **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling **Overall Length:** 0.766 inches **Overall Diameter:** 1.281 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Back shell Mating End Quantity: 1 **Contact Position Arrangement Style:** 16-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 18.0 Shell Type: Solid **Connector Locking Method: Bayonet latch End Application:** B-1b aircraft **Thread Length:** 0.219 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.938 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

## NSN 5935-01-194-9242 Electrical Plug Connector - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Heavier nickel plating required for emi/rfi protection
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0