Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-194-9243

| Thread Classe |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 0.766 inches |
| Overall Diameter: |
| 1.281 inches |
| Environmental Protection: |
| Moisture proof and salt water resistant and vibration proof |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 16-35 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 30.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| End Application: |
| B-1b aircraft |
| Thread Length: |
| 0.219 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.938 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| |

NSN 5935-01-194-9243

Electrical Plug Connector - Page 2 of 2



Criticality Code Justification: Feat **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy Shell Surface Treatment: Nickel **Included Contact Quantity:** 55 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Special Features:** Heavier nickel plating required for emi/rfi protection **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.055 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0