Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-194-9261

Straight Ype Overal Length: 7.595 inches Overal Height: 0.815 inches Overal Width: 0.590 inches Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Norremovable single mating end single contact grouping Polarization Method: Mating end Contact Maximum Current Rating In Amps: 30 single mating end single contact grouping Polarization Method: Mating end Contact Locking Method: Friction End Application: 1440-01-04-9834 Comper alloy single mating end single contact grouping Contact Surface Treatment: Tosigle mating end single contact grouping Contact Surface Treatment: Plasic polyester single mating end single contact grouping Contact Surface Treatment: Tasje diating end single contact grouping Imself mating end single contact grouping Contact Surface Treatment:	De du Stude
Overall Leight: 7.595 inches Overall Height: 0.815 inches Overall Width: 0.590 inches Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Mating end Contact Locking Method: Friction End Application: 1440-01104-8934 Terminal Location: Back single mating end single contact grouping Contact Material: Poper alloy single mating end single contact grouping Contact Material: Ti single mating end single contact grouping Contact Surface Treatment: Plastic polyseter single mating end single contact grouping Contact Material: Plastic polyseter single mating end single contact grouping Contact Material: Plastic polyseter single mating end single	Body Style:
7.595 inclust Overall Height: 0.815 inclust Overall Width: 0.590 inclust Unthreaded Mounting Hole Diameter: 0.112 inclust Distance Between Mounting Facility Centers: 2.275 inclust Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: 3.0 single mating end single contact grouping Polarization Method: Hating End Yeitoin Polarization Method: Friction End Application: Yeitoin Yeitoin Context Material: Copper alloy single mating end single contact grouping Contact Material: Gouper alloy single mating end single contact grouping Contact Material: Polarization Method: Terminal Location: Gouper alloy single mating end single contact grouping Contact Material: Polarization Method: Insingle mating end single contact grouping Contact Material: Polarizatin Met	
Overall Height: 0.815 inches Overall Widht: 0.590 inches Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removabile single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Contect Locking Method: Friction End Application: 1440-01-104-9834 Corper alloy single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Material: Tin single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Contact Surface Treatment: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material Specification: Mil-p-46141 splictification Mil-p-	-
0.815 indes Overall Width: 0.590 inches Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Surface Treatment: This single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material Que-of-30 federal specificationo	
Overall Width: 0.590 inches Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Norremovable single mating end single contact grouping Contact Removability: Norremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Material: The solder lug single mating end Thereit Material: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Surface Treatment: The solder lug single mating end single contact grouping C	-
0.590 inches Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Norremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tistic polyester single mating end single contact grouping Contact Surface Treatment: Plastic polyester single mating end single contact grouping Contact Material Poelfication: Tab, solder lug single mating end single contact grouping Contact Material Specification: Plastic polyester single mating end single contact grouping Contact Surface Treatment: Tab, solder lug single mating end si	
Untriverded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating in Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Th single mating end single contact grouping Contact Surface Treatment: Th single mating end single contact grouping Contact Surface Treatment: Th single mating end single contact grouping Contact Material: Plastic polyester single mating end Solder lug single mating end single contact grouping Contact Material Specification: Cap-6-530 federal specification single material response single mating end single contact grouping Contact Material Specification: Cap-6-530 federal specification single material response single mating end single contact grouping Contact Material Specification: Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping Mil-p-46161 military specification single material response single mating end single contact grouping Single mating end single contact grouping Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping Single Material Specification single material response single mating end Single Material Specification Single material response single mating end Single Material Specification Single Material Specification Single Materia	
0.112 inches Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Insert Material: Plastic polyester single mating end single contact grouping Contact Material Plastic polyester single mating end single contact grouping Contact Surface Treatment: Tab, solder lug single mating end single contact grouping Contact Material Que-c-530 federal specification: Mi-p-46161 military specification single material response single mating end single contact grouping Insert Material Specification </td <td></td>	
Distance Between Mounting Facility Centers: 7.275 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Material: Tin single mating end single contact grouping Misret Material: Plastic polyester single mating end Single mating end single contact grouping Contact Material: Plastic polyester single mating end Single mating end single contact grouping Misret Material Plastic polyester single mating end Single mating end single contact grouping Contact Material: Plastic polyester single mating end Single ficture in the single contact grouping Contact Material Specification: Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping end Single mating end	-
7.275 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Plastic polyester single mating end single contact grouping Insert Material: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material Specification: Quarc-530 federal specification single material response single mating end single contact grouping Insert Material Specification Mil-p-46161 military specification single material response single mating end Insert Material Specification </td <td></td>	
Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Ti single mating end single contact grouping Insert Material: Plastic polyester single mating end single contact grouping Contact Surface Treatment: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material Specification: Qac-c530 federal specification single material response single mating end single contact grouping end single contact grouping end single contact grouping end single contact grouping end finaterial response single mating end single contact grouping end single contact grouping end end single contact grouping end	
1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Th single mating end single contact grouping Insert Material: Plastic polyester single mating end Contact Material: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material Qia-c-530 federal specification Mitp-46161 military specification single material response single mating end single contact grouping Mitp-46161 military specification single material response single mating end Hulp-46161 military specification single material response single mating end Single mating end single contact grouping <	
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Nating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Fortict Surface Treatment: Tin single mating end single contact grouping Parential Type: Pash: polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material Que-s530 federal specification single material response single mating end single contact grouping Insert Material Specification Mil-p-46161 military specification single material response single mating end single contact grouping Contact Material Specification Ga-c-530 federal specification single material response single mating end single contact grouping	Mating End Quantity:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Torminal Type: Tab, solder lug single mating end single contact grouping Contact Material: Plastic polyester single mating end single contact grouping Contact Material: Qac-530 federal specification: Qac-530 federal specification Milp-46161 military specification single material response single mating end single contact grouping Included Contact Quantity: 252 single mating end single contact grouping	
Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material: Qac-530 federal specification: Qac-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end single contact grouping Included Contact Quantity: 252 single mating end single contact grouping	Contact Removability:
3.0 single mating end single contact grouping Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material: Qrc-530 federal specification Mil-p-46161 military specification single material response single mating end single contact grouping Insert Material Specification Mil-p-46161 military specification single material response single mating end single contact grouping Mil-p-46161 military specification single material response single mating end Helded Contact Quantity: 252 single mating end single contact grouping	Nonremovable single mating end single contact grouping
Polarization Method: Mating end Connector Locking Method: Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material: Qr-c-530 federal specification Qu-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping	Contact Maximum Current Rating In Amps:
Mating endConnector Locking Method:FrictionFind Application:1440-01-104-9834Terminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingHaterial:Plastic polyester single mating endForminal Type:Tab, solder lug single mating end single contact groupingContact Material:Qrc-530 federal specificationQac-530 federal specification single material response single mating endInsert Material Specification:Mil-p-46161 military specification single material response single mating endIncluded Contact Quantity:252 single mating end single contact groupingSpecification:Mil-p-46161 military specification single material response single mating endIncluded Contact Quantity:Specification:Specification:Specification:Mil-p-46161 military specification single material response single mating endIncluded Contact Quantity:Specification:Specification:Specification:Mil-p-46161 military specification single material response single mating endIncluded Contact Quantity:Specification:Specification:Specification:Specification:Specification:Specification:Specification:Specification:Specification:Specificatio	3.0 single mating end single contact grouping
Connector Locking Method:FrictionEnd Application:1440-01-104-9834Terminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyester single mating endPlastic polyester single mating end single contact groupingContact Material Specification:Qac-530 federal specification single material response single mating endInsert Material Specification:Mil-p-46161 military specification single material response single mating endIncluded Contact Quantity:252 single mating end single contact groupingShelf Life:	Polarization Method:
Friction End Application: 1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end I reminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end Insert Material Specification single material response single mating end Insert Material Specification single material response single mating end Single Contact Quantity: 252 single mating end single contact grouping	Mating end
End Application:1440-01-104-9834Terminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyester single mating endTerminal Type:Tab, solder lug single mating end single contact groupingContact Material Specification:Qq-c-530 federal specification single material response single mating end single contact groupingInsert Material Specification:Mil-p-46161 military specification single material response single mating endIncluded Contact Quantity:252 single mating end single contact groupingShelf Life:	Connector Locking Method:
1440-01-104-9834 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping	Friction
Terminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyester single mating endTerminal Type:Tab, solder lug single mating end single contact groupingContact Material Specification:Qq-c-530 federal specification single material response single mating end single contact groupingInsert Material Specification:Mil-p-46161 military specification single material response single mating endIncluded Contact Quantity:252 single mating end single contact grouping	End Application:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Single mating end single contact grouping Shelf Life:	1440-01-104-9834
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Terminal Location:
Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Back single mating end single contact grouping
Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Contact Material:
Tin single mating end single contact grouping Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Specification: 252 single mating end single contact grouping Shelf Life:	Copper alloy single mating end single contact grouping
Insert Material: Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Contact Surface Treatment:
 Plastic polyester single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life: 	Tin single mating end single contact grouping
Terminal Type: Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Insert Material:
 Tab, solder lug single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life: 	Plastic polyester single mating end
Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Terminal Type:
Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Tab, solder lug single mating end single contact grouping
Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Contact Material Specification:
Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Qq-c-530 federal specification single material response single mating end single contact grouping
Included Contact Quantity: 252 single mating end single contact grouping Shelf Life:	Insert Material Specification:
252 single mating end single contact grouping Shelf Life:	Mil-p-46161 military specification single material response single mating end
Shelf Life:	Included Contact Quantity:
	252 single mating end single contact grouping
	Shelf Life:
N/a	N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-46161 spec.