

View Online at <https://aerobasegroup.com/nsn/5935-01-194-9566>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight type

**Overall Length:**

Between 3.540 inches and 3.560 inches

**Overall Height:**

0.565 inches

**Overall Width:**

0.250 inches

**Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Mounting Facility Centers:**

3.300 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**End Application:**

1425-01-106-3089

**Thread Length:**

0.130 inches

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.856 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end or mil-m-24519, type gpt-30f military specification single material response single mating end or mil-p-46174, class 40, grade e military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

54 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Jackscrew type-male and location-left hand and jackscrew type-female and location-right hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.054 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-55302/58 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--