

View Online at <https://aerobasegroup.com/nsn/5935-01-194-9617>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.568 inches

Overall Diameter:

0.312 inches

Environmental Protection:

Corrosion resistant

Distance From Mounting Shoulder To Front Face:

0.500 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

Insert Material:

Plastic fluorocarbon all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, cl 2 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550, cl 4 military specification 2nd treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 h federal specification single material response all mating ends single contact grouping

Shell Material:

Metal

Shell Surface Treatment:

Passivate

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.