# NSN 5935-01-195-2035

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-195-2035 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.219 inches **Overall Diameter:** 1.719 inches **Environmental Protection:** Corrosion resistant and moisture resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 21-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 550.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Operating Tempurature Rating:** 302.0 degrees fahrenheit Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.188 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-01-195-2035

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic epoxy single mating end and glass fiber single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy 6061

#### **Shell Surface Treatment:**

Cadmium and nickel

## **Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification 1st treatment response and qq-n-290 federal specification 2nd treatment response

#### **Shell Material Specification:**

Qq-a-200 federal specification single material response

#### **Included Contact Quantity:**

79 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.079 gold grains, troy

## **Precious Material:**

Gold

#### **Thread Series Designator:**

Unef

#### Shelf Life:

N/a

# **Unit Of Measure:**

## Demilitarization:

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.