# NSN 5935-01-195-2243

Right-hand and right-hand and right-hand

**Environmental Protection:**Cold resistant and heat resistant

**Threaded Device Type:** 

**Distance Between Mounting Facility Centers:** 

Thread Class: 2a and 2b and 2a Thread Direction:

Body Style:
Straight shape
Overall Length:
1.560 inches
Overall Height:
0.840 inches
Overall Width:
0.460 inches

1.250 inches

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-195-2243

Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Removable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
750.0 single mating end 1st contact grouping
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 40
Thread Size:
0.138 inches and 0.138 inches and 0.112 inches
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

# NSN 5935-01-195-2243

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end 1st contact grouping

## **Criticality Code Justification:**

Feat

## **Terminal Type:**

Solder well single mating end 1st contact grouping

## **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end 1st contact grouping

### **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

8 single mating end 1st contact grouping

#### **Included Contact Type:**

Round pin single mating end 1st contact grouping

#### **Special Features:**

Contact cavities a, c, e, h, l, n, p, r, s, t, w, and x are blank

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.008 gold grains, troy

# **Precious Material:**

Gold

# Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

## **Unit Of Measure:**

\_\_

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.