NSN 5935-01-195-2247

Right-hand and right-hand and right-hand

Environmental Protection:Cold resistant and heat resistant

Threaded Device Type:

Distance Between Mounting Facility Centers:

Thread Class: 2a and 2b and 2a Thread Direction:

Body Style:
Straight shape
Overall Length:
1.560 inches
Overall Height:
0.840 inches
Overall Width:
0.460 inches

1.250 inches

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-195-2247

Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Removable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
750.0 single mating end 1st contact grouping
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 40
Thread Size:
0.138 inches and 0.138 inches and 0.112 inches
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

NSN 5935-01-195-2247

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end 1st contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

18 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end 1st contact grouping

Special Features:

Contact cavities h and w are empty

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.018 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.