

View Online at <https://aerobasegroup.com/nsn/5935-01-195-2252>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.560 inches

**Overall Height:**

0.840 inches

**Overall Width:**

0.460 inches

**Environmental Protection:**

Cold resistant and heat resistant

**Distance Between Mounting Facility Centers:**

1.250 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20 20-20 single mating end

**Contact Removability:**

Removable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

750.0 single mating end 1st contact grouping

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

32 and 32 and 40

**Thread Size:**

0.138 inches and 0.138 inches and 0.112 inches

**Terminal Location:**

Back single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end 1st contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Solder well single mating end 1st contact grouping

**Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end 1st contact grouping

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

10 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end 1st contact grouping

**Special Features:**

Contact cavities b, c, e, f, h, j, l, m, n, and p are blank; the contact in cavity v has a cable, adapter, coaxial

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.