

View Online at <https://aerobasegroup.com/nsn/5935-01-195-2312>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

2.938 inches

**Body Angle In Deg:**

135.0

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

**Cable Entrance Diameter:**

Between 0.350 inches and 0.625 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24-10 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

73.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Connector End:**

5.272 inches

**Distance From Centerline To Cable End:**

3.625 inches

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 175.0 degrees celsius

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.500 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Rubber silicone class q single mating end

**Contact Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium and chromate and nickel

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.035 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3409 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-5015 spec.