Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-195-2319

Body Style:

Straight shape threaded

Overall Length:

0.979 inches

Overall Diameter:

0.625 inches

Environmental Protection:

Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.609 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

12267 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber synthetic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

3 single mating end single contact grouping

NSN 5935-01-195-2319

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Solder flange mtd

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.003 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0