NSN 5935-01-195-2319

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-195-2319

Body Style: Straight shape threaded **Overall Length:** 0.979 inches **Overall Diameter:** 0.625 inches **Environmental Protection:** Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 0.609 inches **Mating End Quantity: Contact Position Arrangement Style:** 12267 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:**

Cadmium

Included Contact Quantity:

3 single mating end single contact grouping

NSN 5935-01-195-2319

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mtd
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.003 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0