

View Online at <https://aerobasegroup.com/nsn/5935-01-195-6030>

Thread Class:

2b

Thread Direction:

Right-hand

Overall Width:

0.782 inches

Body Angle In Deg:

90.0

End Application:

Ticonderoga class cg (47); helicopter, advance attack, ah-1w; aircraft, orion p-3; nimitz class cvn; aircraft, (ac-130h, mc-130h, ec-130e, hc-130

Cable Opening Diameter:

0.365 inches

Distance From Centerline To Connector End:

0.751 inches

Distance From Centerline To Cable End:

1.290 inches

Cable Opening Quantity:

1

Mounting Facility Type And Quantity:

1 threaded coupling

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Material:

Aluminum alloy

Material:

Aluminum alloy

Surface Treatment:

Anodize

Style Designator:

Clamp, angle tie strap type

Surface Treatment:

Anodized

Test Data Document:

81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UN2f

Specification Data:

81349-mil-c-85049/55 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A10100