NSN 5935-01-196-4804

Thread Class:

Special Features:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-196-4804

| Till Cad Olass. | |
|--|--|
| 2a and 2b | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Hood, top opening w/clamp | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 20 20-20 single mating end | |
| Contact Removability: | |
| Nonremovable single mating end single contact grouping | |
| Polarization Method: | |
| Jackscrew | |
| Shell Type: | |
| Hood, top opening | |
| Connector Locking Method: | |
| Jackscrew-socket | |
| Connector Cable Strain Relief Method: | |
| Cable clamp | |
| Terminal Location: | |
| Back single mating end single contact grouping | |
| Contact Material: | |
| Copper alloy single mating end single contact grouping | |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping | |
| Criticality Code Justification: | |
| Feat | |
| Terminal Type: | |
| Solder well single mating end single contact grouping | |
| Shell Material: | |
| Aluminum | |
| Shell Surface Treatment: | |
| Cadmium | |
| Included Contact Quantity: | |
| 9 single mating end single contact grouping | |
| Included Contact Type: | |
| Round socket single mating end single contact grouping | |
| | |

Contacts are only in positions a, b, d, h, k, p, s, u and w

NSN 5935-01-196-4804

Electrical Plug Connector - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.009 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0