Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-196-5149

Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight shape, rectangular
Overall Length:
3.187 inches
Overall Height:
0.900 inches
Overall Width:
2.592 inches
Environmental Protection:
Corrosion resistant and vibration resistant and thermal shock resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.468 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.280 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Jackscrew
End Application:
Support equipment, a-10 aircraft
Thready Qty Per Inch (tpi):
40
Thread Size:
0.125 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Conner allow single mating and single contact grouping

Copper alloy single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade d, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl

2 federal specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f or gdi-30f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

56 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.056 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28731/13 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0