NSN 5935-01-196-5712



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-196-5712 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.405 inches **Overall Height:** 1.328 inches **Overall Width:** 1.328 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.431 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** "18-8, 22-404" single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 23.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1500.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

Connector Locking Method:

Bayonet pin

NSN 5935-01-196-5712

Electrical Receptacle Connector - Page 2 of 2



Thread Length:
0.290 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.062 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
8 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.008 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.