Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-196-6913

Thread	Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

3.000 inches

Overall Height:

0.669 inches

Overall Width:

0.286 inches

Distance Between Mounting Facility Centers:

2.800 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end



Contact Surface Treatment Specification: Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping and gq-n-290, class 1 federal specification 2nd treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-613, comp 260, 1/2 h federal specification single material response single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Chromate **Shell Surface Treatment Specification:** Mil-c-5541 military specification single treatment response **Shell Material Specification:** Qq-a-200 federal specification single material response **Insert Material Specification:** Mil-p-20693, type 1 military specification single material response single mating end **Included Contact Quantity:** 41 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Contacts no. 2, 4, 10, 16, 17, 36, 37, 42, 44, 50 and 52 omitted **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.052 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-g-45204 spec.