NSN 5935-01-197-1961

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-197-1961

Body Style:
Straight shape
Overall Length:
5.600 inches
Overall Height:
0.875 inches
Overall Width:
0.630 inches
Unthreaded Mounting Hole Diameter:
0.141 inches
Distance Between Mounting Facility Centers:
4.500 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
6920-01-129-5722
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Steel comp 303
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:

onen ourrace Treatment opeemeat

Qq-p-35 federal specification single treatment response

NSN 5935-01-197-1961

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-20693, type 1 military specification single material response single mating end

Included Contact Quantity:

200 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.200 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-20693 spec.