NSN 5935-01-197-2627

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-197-2627	
Thread Class:	
2a and 2b and 2a	
Thread Direction:	
Right-hand and right-hand	
Body Style:	
Straight shape	
Overall Length:	
3.130 inches	
Overall Height:	
0.960 inches	
Overall Width:	
0.380 inches	
Environmental Protection:	
Shock resistant and vibration resistant and corrosion resistant and humidity resistant	
Distance Between Mounting Facility Centers:	
Between 2.800 inches and 2.807 inches	
Threaded Device Type:	
Coupling facility and mounting stud	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
74 single mating end	
Contact Removability:	

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-01-197-2627

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty mdg military specification single material response single mating end

Included Contact Quantity:

74 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-female and location-right handandjackscrew type-male and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.074 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.