NSN 5935-01-198-1781

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-198-1781

view Online at https://defobasegroup.com/hish/0303-01-130-1701
Body Style:
Straight type
Overall Length:
1.850 inches
Overall Width:
0.250 inches
Body Height:
0.335 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and shock resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 2
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Solder stud single mating end single contact grouping
Included Contact Quantity:
30 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping

Precious Material And Weight: 0.030 gold grains, troy

Contact surfaces gold

Precious Material And Location:

NSN 5935-01-198-1781

Precious Material:

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/63 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030h0