Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-198-3211

Body Style:

Straight type

Overall Length:

1.350 inches

Overall Height:

0.735 inches

Overall Width:

0.250 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

1.100 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 2

federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single material response single contact grouping or qq-w-321 federal specification single material response single materia

Insert Material Specification:

Mil-m-24519 military specification single material response single mating and



Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 10 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.010 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.