

View Online at <https://aerobasegroup.com/nsn/5935-01-198-6241>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, external/internal coupling

Overall Length:

1.252 inches

Overall Height:

1.342 inches

Overall Width:

0.650 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

End Application:

1560-01-111-1138

Thready Qty Per Inch (tpi):

28 and 28

Thread Size:

0.438 inches and 0.438 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2, grade c military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket 1st mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-a-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

81349-mil-a-55339/32 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.