

View Online at https://aerobasegroup.com/nsn/5935-01-198-6255

| Fhread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.549 inches |
| Dverall Height: |
| Between 1.552 inches and 1.573 inches |
| Overall Width: |
| Between 1.552 inches and 1.573 inches |
| Environmental Protection: |
| Cold resistant and heat resistant |
| Inthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| .250 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| .250 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.556 inches and 0.566 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| |
| Polarization Method: |
| Keyway or multiple keyway |
| nsert Position In Deg: |
| 356.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Thready Qty Per Inch (tpi): |
| 8 |
| Thread Size: |
| .312 inches |
| nsert Material: |
| Rubber single mating end |
| Shell Material: |
| Aluminum alloy |
| |

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416 ty ii, cl 3 federal specification 1st treatment response and qq-n-290 federal specification 2nd treatment response

Special Features:

Insert configuration 22-13

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0