

View Online at <https://aerobasegroup.com/nsn/5935-01-198-6992>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/screw locks

**Overall Length:**

4.355 inches

**Overall Height:**

1.050 inches

**Overall Width:**

0.405 inches

**Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Polarization Method:**

Mating end

**Connector Locking Method:**

Jackscrew-socket

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Insert Material:**

Plastic diallyl phthalate glass filled or plastic polyester glass filled single mating end

**Insert Material Specification:**

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

**Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-55302/113 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.