NSN 5935-01-198-7918

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-198-7918

Body Style: Right angle type **Overall Length:** 6.180 inches **Overall Height:** 0.710 inches **Overall Width:** 0.280 inches **Unthreaded Mounting Hole Diameter:** 0.067 inches **Distance Between Mounting Facility Centers:** 6.000 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper alloy single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 3rd treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-p-19833 ty gdi-30f military specification single material response single mating end **Included Contact Quantity:**

Contact surfaces gold

Precious Material And Location:

Included Contact Type:

112 single mating end single contact grouping

Round pin single mating end single contact grouping

NSN 5935-01-198-7918

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.112 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.