## NSN 5935-01-199-2723

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-199-2723

9· · · · · · · · · · · · · · · · · · ·
Body Style:
Straight shape, external coupling
Overall Length:
0.703 inches
Overall Height:
1.453 inches
Overall Width:
1.453 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
Between 0.317 inches and 0.322 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
20-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
30.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Gold single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Stainless steel

## NSN 5935-01-199-2723

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Passivate
Included Contact Quantity:
79 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.079 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27499 government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-38999 spec.