Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-199-2729

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Right angle type

Overall Length:

3.350 inches

Overall Height:

0.465 inches

Overall Width:

0.250 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

3.100 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1

federal specification 2nd treatment response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Criticality Code Justification:

Feat

Terminal Type: Wire wrap single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14g military specification single material response single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 49 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Contact position no. 13 missing **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.049 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.