# NSN 5935-01-199-4439

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-199-4439 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.850 inches **Overall Diameter:** 0.312 inches **Environmental Protection:** Shock proof and vibration proof **Cable Entrance Diameter:** 0.160 inches **Distance From Mounting Shoulder To Front Face:** 0.450 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut Thread Length: 0.190 inches Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-01-199-4439

Electrical Receptacle Connector - Page 2 of 2



^^	ntact	Surfa	co Tr	aatm	ont.
JO	ntact	Surra	ce in	eaum	ent:

Gold single mating end single contact grouping

**Insert Material:** 

Plastic polytetrafluoroethylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, gr c, cl 2 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530, 1/2 h federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Stainless steel

#### **Shell Material Specification:**

Qq-s-764, cl 303, cond a federal specification single material response

#### **Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

#### **Included Contact Quantity:**

1 single mating end single contact grouping

## **Bushing Accommodation Hole Shape:**

Round w/flat

## **Included Contact Type:**

Coaxial socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surface gold

# **Precious Material And Weight:**

0.005 gold grains, troy

#### **Precious Material:**

Gold

# **Thread Series Designator:**

Uns

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.