## NSN 5935-01-199-7161

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-199-7161

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

**4.343** inches

**Overall Height:** 

0.406 inches

**Overall Width:** 

0.328 inches

**Unthreaded Mounting Hole Diameter:** 

0.116 inches

**Distance Between Mounting Facility Centers:** 

4.031 inches

**Board Accommodated Length:** 

3.578 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.071 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

575.0 single mating end single contact grouping

**Polarization Method:** 

Inter-contact polarizing keys

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, cl 2 military specification 1st treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

# NSN 5935-01-199-7161

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-19833, ty gdi-30 military specification single material response single mating end

## **Included Contact Quantity:**

44 single mating end single contact grouping

## **Included Contact Type:**

Bifurcated accordian leaf spring single mating end single contact grouping

#### **Special Features:**

Polarizing key located position 20

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.044 gold grains, troy and 0.044 silver grains, troy

#### **Precious Material:**

Gold and silver

#### Shelf Life:

N/a

#### **Unit Of Measure:**

## Demilitarization:

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.