

View Online at <https://aerobasegroup.com/nsn/5935-01-200-1476>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Rectangular shape

**Overall Length:**

3.028 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 2.574 inches and 2.582 inches

**Overall Height:**

Between 1.230 inches and 1.260 inches

**Overall Width:**

1.170 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.558 inches and 0.566 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**End Application:**

An/bld-1

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074, grade b, cl 3 or 4 military specification single treatment response

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Included Contact Quantity:**

32 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.032 gold grains, troy and 0.032 silver grains, troy

**Precious Material:**

Gold and silver

**Test Data Document:**

81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-83733/5 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26074 spec.