

View Online at <https://aerobasegroup.com/nsn/5935-01-200-4003>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.990 inches

Overall Height:

0.796 inches

Distance Between Mounting Facility Centers:

0.656 inches

Cable Entrance Diameter:

Between 0.139 inches and 0.143 inches

Distance From Mounting Shoulder To Front Face:

0.508 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and qq-n-290 federal specification 3rd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.