Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-200-4952

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 2.000 inches |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 2.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.260 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.500 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.500 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Maximum Current Rating In Amps: |
| 22.0 single mating end single contact grouping |
| Shell Type: |
| Solid |
| Thready Qty Per Inch (tpi): |
| 10 |
| Thread Size: |
| 1.500 inches |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Shell Material: |
| Steel or aluminum |
| Shell Surface Treatment: |
| Passivate or anodize |
| Included Contact Quantity: |
| 12 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0