NSN 5935-01-200-6318

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-200-6318 **Body Style:** Straight shape **Overall Length:** Between 1.350 inches and 1.385 inches **Overall Height:** 1.170 inches **Overall Width:** 3.028 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock resistant and thermal shock resistant **Unthreaded Mounting Hole Diameter:** Between 0.276 inches and 0.286 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.558 inches and 0.566 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.574 inches and 2.582 inches **Distance From Mounting Shoulder To Front Face:** Between 0.519 inches and 0.534 inches **Mating End Quantity: Contact Position Arrangement Style:** "18, 018" single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **End Application:** E-3a acft

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-200-6318

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Nickel Shell Surface Treatment Specification: Mil-c-26074, grade b, cl 3 or 4 military specification single treatment response Shell Material Specification: Qq-a-591 federal specification single material response Included Contact Quantity: 18 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features:
Shell Surface Treatment Specification: Mil-c-26074, grade b, cl 3 or 4 military specification single treatment response Shell Material Specification: Qq-a-591 federal specification single material response Included Contact Quantity: 18 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping
Mil-c-26074, grade b, cl 3 or 4 military specification single treatment response Shell Material Specification: Qq-a-591 federal specification single material response Included Contact Quantity: 18 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping
Shell Material Specification: Qq-a-591 federal specification single material response Included Contact Quantity: 18 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping
Qq-a-591 federal specification single material response Included Contact Quantity: 18 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping
Included Contact Quantity: 18 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping
18 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping
Included Contact Type: Round pin single mating end single contact grouping
Round pin single mating end single contact grouping
Special Features
opecial i eatures.
Furnished items - mounting nut
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.018 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-83733/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-26074 spec.