NSN 5935-01-200-6644

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-200-6644

Straight type			
Overall Length:			
2.316 inches			
Overall Width:			
0.420 inches			
Body Height:			
0.750 inches			
Environmental Protection:			
Heat resistant and cold resistant			
Mating End Quantity:			
1			
Contact Position Arrangement Style:			
1 row of contacts non-inserted board single mating end			
Contact Removability:			
Nonremovable single mating end single contact grouping			
Contact Maximum Current Rating In Amps:			
7.0 single mating end single contact grouping			
Contact Maximum Ac Voltage Rating In Volts:			
250.0 single mating end single contact grouping			
Polarization Method:			
Shell			
Official			
Connector Locking Method:			
Connector Locking Method:			
Connector Locking Method: Friction			
Connector Locking Method: Friction Terminal Location:			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material:			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material:			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type:			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Shell Material:			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Shell Material: Metal			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Shell Material: Metal Included Contact Quantity:			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Shell Material: Metal Included Contact Quantity: 15 single mating end single contact grouping			
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Pin single mating end single contact grouping Shell Material: Metal Included Contact Quantity: 15 single mating end single contact grouping Included Contact Type:			

NSN 5935-01-200-6644

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0