# NSN 5935-01-200-8276

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-200-8276

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

**4.370** inches

**Overall Height:** 

0.607 inches

**Overall Width:** 

0.531 inches

#### **Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

0.128 inches

#### **Distance Between Mounting Facility Centers:**

4.100 inches

#### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

# **Mating End Quantity:**

1

### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

# **Connector Locking Method:**

Friction

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Copper single mating end single contact grouping and gold single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Contact Surface Treatment Specification:**

Mil-c-14550 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, ty ii, grade c military specification 2nd treatment response single mating end single contact grouping

# **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30 military specification single material response single mating end

# **Included Contact Quantity:**

35 single mating and single contact grouping

# NSN 5935-01-200-8276

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Hermaphrodite single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.035 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-21097/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: