Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-200-9331

······
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
3.426 inches
Overall Width:
0.350 inches
Body Height:
0.350 inches
Distance Between Mounting Facility Centers:
3.240 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1200.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil a 45204 military aposition single treatment response single

Mil-g-45204 military specification single treatment response single mating end single contact grouping



Terminal Type: Pin single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 92 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.092 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.