

View Online at <https://aerobasegroup.com/nsn/5935-01-200-9643>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

Between 0.994 inches and 1.036 inches

Overall Diameter:

0.593 inches

Environmental Protection:

Cold resistant and heat resistant and weatherproof

Cable Entrance Diameter:

Between 0.144 inches and 0.149 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365a, type 2, cl a federal specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Insert Material Specification:

Mil-p-19468a military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.