NSN 5935-01-201-1447

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-201-1447 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 38.9 millimeters **Overall Diameter:** 37.4 millimeters **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 17-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Detent **End Application:** 1520-01-106-9519 **Thread Size:** 25.0 millimeters **Thread Pitch In Millimeters:** 1.00 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-201-1447Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Tolerance Class:
6g internal
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m
Specification Data:
81349-dod-c-38999/47 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0